

	Cylinder	Bore (mm)	Stroke (mm)	Displacement effective (ccm)	Compression rate	Performance kW/HP at 1/min	Maximum torque (Nm) at 1/min	Fuel	Maximum Speed (km/h)	0 - 100 km/h (s)	80 - 120 km/h (s) - 4th gear	80 - 120 km/h (s) - 5th gear	80 - 120 km/h (s) - 6th gear	1000 m standing start
---	----------	-----------	-------------	------------------------------	------------------	----------------------------	------------------------------	------	----------------------	------------------	------------------------------	------------------------------	------------------------------	-----------------------

<b>Cooper D Performance upgrade</b> for MINI R55 with 1.6l Diesel engine (W16D16O0)														
<b>AC Schnitzer MINI Cooper D</b>	4 in line	75,0	88,3	1560	18,0 : 1	100/136 at 4000	288 (308*) at 1900-2200	Diesel	195 (-)	10,1 (-)	7,1 (-)	8,6 (-)	n/a	n/a
MINI Cooper D (standard)	4 in line	75,0	88,3	1560	18,0 : 1	80/110 at 4000	240 (260*) at 1750-2000	Diesel	193 (188)	10,4 (10,9)	7,9 (-)	10,2 (-)	n/a	32,9 (33,1)

\* = Overboost ( ) = automatic version

<b>Cooper D Performance upgrade</b> for MINI R56 with 1.6l Diesel engine (W16D16O0)														
<b>AC Schnitzer MINI Cooper D</b>	4 in line	75,0	88,3	1560	18,0 : 1	100/136 at 4000	288 (308) at 1900-2200	Diesel	200 (-)	9,6 (-)	6,6 (-)	7,9 (-)	n/a	n/a
MINI Cooper D (standard)	4 in line	75,0	88,3	1560	18,0 : 1	80/110 at 4000	240 (260) at 1750-2000	Diesel	195 (190)	9,9 (10,3)	7,4 (-)	9,5 (-)	n/a	32,3 (32,5)

\* = Overboost ( ) = automatic version

<b>Cooper S Performance upgrade</b> for MINI R56 with 1.6l engine (N14B16O0)														
<b>AC Schnitzer MINI Cooper S</b>	4 in line	77,0	85,8	1598	10,5 : 1	166/226 at 5500	265 (285*) at 1650-5000 (1750-4500*)	ROZ 98-100	243 (-)	6,4 (-)	n/a	5,1 (-)	n/a	n/a
MINI Cooper S (standard)	4 in line	77,0	85,8	1598	10,5 : 1	128/175 at 5500	240 (260*) at 1600-5000 (1700-4500*)	ROZ 91-98	225 (220)	7,1 (7,3)	5,6 (-)	7,0 (-)	n/a	27,6 (27,9)

\* = Overboost ( ) = automatic version

<b>Cooper S Performance upgrade</b> for MINI R55 with 1.6l engine (N14B16O0)														
<b>AC Schnitzer MINI Cooper S</b>	4 in line	77,0	85,8	1598	10,5 : 1	166/226 at 5500	265 (285*) at 1650-5000 (1750-4500*)	ROZ 98-100	242	6,9 (7,1)	n/a	5,7 (-)	n/a	n/a
MINI Cooper S (standard)	4 in line	77,0	85,8	1598	10,5 : 1	128/175 at 5500	240 (260*) at 1600-5000 (1700-4500*)	ROZ 91-98	224 (219)	7,6 (7,8)	5,9 (-)	7,6 (-)	n/a	28,0 (28,3)

\* = Overboost ( ) = automatic version